

<p>Safety distance from source of hazard 120 mm</p>	<p>Revolving door height 2000/2200 mm (frame 1800/2000 mm)</p> <p>All doors with QR 40 lateral lock strut</p> <p>Door cross brace as upper closure. Application as cable channel also possible.</p> <p>Locking via latch & deadbolt lock with profile cylinder Aluminium handle fitting (consisting of 2 turnable handles)</p> <p>Finger safeguard optional, see accessories</p> <p>Universal construction method for DIN left / right assembly</p>	<p>Opening direction from outside</p> <p>DIN left</p> <p>DIN right</p>
--	---	--

System height 2000 mm | Universal left / right

Order no.	Colour group 2	Colour group 3	Colour group 4	Door
	RAL	RAL	RAL	in mm W x H
BTLR18010019	2-7035	3-xxxx	4-xxxx	1000 x 2000 mm

System height 2200 mm | Universal left / right

Order no.	Colour group 2	Colour group 3	Colour group 4	Door
	RAL	RAL	RAL	in mm W x H
BTLR20010019	2-7035	3-xxxx	4-xxxx	1000 x 2200 mm

Example for the correct method of ordering

Order no. **BTLR18010019** + Colour group 2 + RAL colour no. **7035** = Complete order no **BTLR18010019-2-7035**

Specifications are subject to technical changes without notice
 Other widths and heights are available upon request: Phone: 0049 - (0) 5223-79 19 95 -0 | Fax: 0049 - (0) 5223-79 19 95 - 90